

Ordering Information

Field Adjustable

SPAH - ¹2 - ²2M - ³C1 - ⁴QC1 - ⁵T1

Factory Preset

SPFH - ¹30F - ²2M - ³C1 - ⁴QC1 - ⁵T1

1 - Pressure Selection:

Field Adjustable - Select Model Code

Insert set point value XXX followed by: R, F, BR, or BF

Model	Adjustment Range	
	PSI	BAR
1	3 - 9	0.2 - 0.6
2	7 - 20	0.5 - 1.4
3	17 - 36	1.2 - 2.5
4	29 - 58	2.0 - 4.0
5	43 - 100	3.0 - 6.9
6	70 - 130	4.8 - 9.0

OR

Set Point	Direction	Description
XXXX	R	PSI Rising Pressure
	F	PSI Falling Pressure
	BR	BAR Rising Pressure
	BF	BAR Falling Pressure

2 - Thread Options:

- 2M - 1/8 NPT male
- 4M - 1/4 NPT male
- 2G - 1/8 BSPP male, G1/8
- 4G - 1/4 BSPP male, G1/4

3 - Circuit:

- C1 - SPDT (Single Pole Double Throw) - 16A, 125/250 VAC
- C2 - SPDT (Single Pole Double Throw) - 22A, 125/250 VAC

4 - Electrical Termination:

- QC1 - Quick Connect 4.8 mm
- QC2 - Quick Connect 6.35 mm

5 - Temperature Rating:

- T1 - 85°C
- T2 - 125°C



Note: Please see page 52 for other available options