

Ordering Information

Field Adjustable

1 2 3 4 5 6 (Optional)
SLBA - 1 - 2M - A - FL - 2 - 7

Factory Preset

1 2 3 4 5 6 (Optional)
SLBF - 30F - 2M - A - FL - 2 - 7

1 - Pressure Selection:

Field Adjustable - Select Model Code

| MODEL | ADJUSTMENT RANGE | |
|-------|------------------|-----------|
| | PSI | BAR |
| 1 | 2 - 20 | 0.1 - 1.4 |
| 2 | 20 - 60 | 1.4 - 4.2 |
| 3 | 50 - 135 | 3.5 - 9.0 |

OR

Insert set point value XXX followed by: R, F, BR, or BF

| Set point | Direction | Description |
|-----------|-----------|----------------------|
| XXXX | R | PSI Rising Pressure |
| | F | PSI Falling Pressure |
| | BR | BAR Rising Pressure |
| | BF | BAR Falling Pressure |

2 - Thread Options:

2M - 1/8 NPT male

3 - Circuit:

- A - SPST (Normally Open)
- B - SPST (Normally Closed)

4 - Electrical Termination:

- FL - Flying Lead 18" long, 18 AWG, IP68 Cap is standard with this option
- FLWF - Flying Lead Weatherpack connector, female, Tower, 10" long leads
- FLWM - Flying Lead Weatherpack connector, male, Shroud, 10" long leads
- FLDP - Flying Lead Deutsch connector, plug, 10" long leads
- FLDR - Flying Lead Deutsch connector, receptacle, 10" long leads
- FLCM - Flying Lead Metripack, male, 150 series, 10" long leads
- FLCF - Flying Lead Metripack, female, 150 series, 10" long leads
- FLPM - Flying Lead Metripack, male, 280 series, 10" long leads
- FLPF - Flying Lead Metripack, female, 280 series, 10" long leads

5 - Diaphragm Material:

2 - EPDM Diaphragm

6 - Options (Omit if not required):

- 7 - Gold Contact, 0.4VA, 30 VDC
- SR - Snubber



Note: Please see page 52 for other available options