

Ordering Information

Field Adjustable **DSPA** - ¹**2** - ²**4M-4M** - ³**C** - ⁴**HC** - ^{5 (Optional)}**1**

Factory Preset **DSPF** - ¹**30F** - ²**4M-4M** - ³**C** - ⁴**HC** - ^{5 (Optional)}**1**

1 - Pressure Selection:

Field Adjustable - Select Model Code

Insert set point value XXX followed by: R, F, BR, or BF

Model	Adjustment Range	
	PSI	BAR
1	10 - 30	0.7 - 2.0
2	25 - 60	1.7 - 4.0

OR

Set Point	Direction	Description
XXXX	R	PSI Rising Pressure
	F	PSI Falling Pressure
	BR	BAR Rising Pressure
	BF	BAR Falling Pressure

2 - Thread Options for both process connections:

4M-4M - 1/4 NPT male

4G-4G - 1/4 BSPP male, G1/4

3 - Circuit:

C - SPDT (Single Pole Double Throw : Normally Open and Normally Closed)

4 - Electrical Termination:

H - DIN 43650A - connector type - male half only (only available in SPDT option)

HC - DIN 43650A PG9/PG11 - connector type (only available in SPDT option)

HN - DIN 43650A 1/2" NPT Conduit (only available in SPDT option)

5 - Options (Omit if not required):

1 - Viton® Diaphragm

2 - EPDM Diaphragm

4 - HNBR Diaphragm

7 - Gold Contact, Snap Action Microswitch @ 20 mA / 12 VDC

8 - 10 amp, Snap Action Microswitch
@ 10(2) 125 VAC (inductive), 6(2) 250 VAC (inductive)



Note: Please see page 52 for other available options