

Ordering Information

Factory Preset

S2TAF or S3TAF - ¹140F - ²4M - ³B - ⁴HC

1 - Temperature Selection:

Insert set point value XXX followed by: R, F.

Set Point	Direction	Description
XXXX	R	°F Rising Temperature
	F	°F Falling Temperature

2 - Thread Options:

Thread Description	S2TAF Model	S3TAF Model
	No Probe	5/8" Probe
1/4 NPT	4M	4M10
3/8 NPT	6M	6M10
1/2 NPT	8M	8M10
3/4-16 SAE with Viton O-ring seal	8S	N/A

* Other Thread and Probe options are available upon request. Consult factory for availability

3 - Circuit:

- A** - SPST (Normally Open)
- B** - SPST (Normally Closed)

4 - Electrical Termination:

S2TAF	S3TAF	
HC	-	- DIN 43650A - connector type (Only available for S2TAF series)
HN	-	- DIN 43650A 1/2" NPT Conduit (Only available for S2TAF series)
	FL	- Flying Lead 18" long, 18 AWG
	FLWF	- Flying Lead Weatherpack connector, female, Tower, 10" long leads
	FLWM	- Flying Lead Weatherpack connector, male, Shroud, 10" long leads
	FLDP	- Flying Lead Deutsch connector, plug, 10" long leads
	FLDR	- Flying Lead Deutsch connector, receptacle, 10" long leads
	FLCM	- Flying Lead Metripack, male, 150 series, 10" long leads
	FLCF	- Flying Lead Metripack, female, 150 series, 10" long leads
	FLPM	- Flying Lead Metripack, male, 280 series, 10" long leads
	FLPF	- Flying Lead Metripack, female, 280 series, 10" long leads
	SP	- 1/4" Spade
	DR	- Integrated Detusch Receptacle - Mates with DT06-2S



*Other material and options available upon request. Please consult factory for details.