

Ordering Information

Factory Preset

1
2
3
4
5

S5TAF or S7TAF - **140R** - **4M08** - **A** - **FL**

1 Model Selection:

- S5TAF** - Approximately 30% of setpoint (see Temperature Selection Table)
- S7TAF** - Approximately <4% of setpoint (see Temperature Selection Table)

2 - Temperature Selection - Standard available setpoints (Fahrenheit Rising):

S5TAF Model	S7TAF Model
130R	120R
140R	140R
150R	160R
160R	170R
170R	180R
180R	
190R	
200R	
220R	

*Other Setpoints are available upon request. Consult factory for availability

3 - Thread Options:

Thread Description	S5TAF Model	S7TAF Model		
	3/4" Probe	1/2" Probe	1" Probe	2" Probe
1/4 NPT	4M12	4M08	4M16	4M32
3/8 NPT	6M12	N/A	6M16	N/A
1/2 NPT	8M12	8M08	8M16	8M32
3/4-16 SAE with Viton O-ring seal	8S12	N/A	8S16	N/A

*Other thread and probe options are available upon request. Consult factory for availability

4 - Circuit:

- A** - SPST (Normally Open)
- B** - SPST (Normally Closed)

5 - Electrical Termination:

- EL** - 1/2" male conduit with 18" long leads. Only available with 8M08 thread
- FL** - Flying Lead 18" long, (20 AWG for S5TAF) (18 AWG for S7TAF)
- FLWF** - Flying Lead Weatherpack connector, female, 10" long leads
- FLWM** - Flying Lead Weatherpack connector, male, 10" long leads
- FLDP** - Flying Lead Deutsch connector, plug, 10" long leads
- FLDR** - Flying Lead Deutsch connector, receptacle, 10" long leads
- FLCM** - Flying Lead, Metripack, male, 150 series, 10" long leads
- FLCF** - Flying Lead, Metripack, female, 150 series, 10" long leads
- FLPM** - Flying Lead Metripack 280 connector, male, 10" long leads
- FLPF** - Flying Lead Metripack 280 connector, female, 10" long leads