

HARNESS ASSEMBLY

Ordering Information





Please refer to page 57 for connector diagram. Not all connectors are offered on page 57 are available as a harness. See ordering code below.

Series	Number of Pins Available
CFPS2	3
FLDP	2, 3, 4
FLDR	2, 3, 4
FLWF	2, 3
FLWM	2, 3
FLCM	2, 3
FLCF	2,3
FLPM	2, 3
FLPF	2, 3

1 - Connector Type:

Series Description

CFPS2 - Metripack 150 P2S Series **FLDP** - Deutsch DT Series Plug **FLDR** - Deutsch DT Series Receptacle **FLWF** - Weather Pack Female (Tower) **FLWM** - Weather Pack Male (Shroud) **FLCM** - Metripack 150 Series Male - Metripack 150 Series Female **FLCF FLPM** - Metripack 280 Series Male **FLPF** - Metripack 280 Series Female

2 - Number of Pins:

2
3 - Select Number of Pins required.

Please see above details for number of pins offered for the connector series.

3 - Wire or Cable Length:

18FL - 18" Flying Lead, 18 AWG, PVC, 600V, UL1015

79FL - 79" Flying Lead, 18 AWG, PVC, 600V, UL1015 **120FL** - 120" Flying Lead, 18 AWG, PVC, 600V, UL1015

- 39" Cable, 20 AWG, PVC, Jacketed with braid/foil shielded
- 79" Cable, 20 AWG, PVC, Jacketed with braid/foil shielded
- 118" Cable, 20 AWG, PVC, Jacketed with braid/foil shielded
- 196" Cable, 20 AWG, PVC, Jacketed with braid/foil shielded

4 - Options: (Optional, blank if standard)

Blank - No Options required

HS - Heat Shrink (For flying lead configuration only)SL - Split Flex (For flying lead configuration only)

ELECTRICAL CONFIGURATION ANFIE



